

- GENERAL NOTES**
- DO NOT SCALE DRAWINGS. THE LOCATIONS OF ALL PIPES SHOWN ON THE DRAWINGS OR SPECIFIED THAT ARE NOT DETAILLED BY THE DRAWINGS ARE APPROXIMATE ONLY. THE EXACT LOCATIONS NECESSARY TO SECURE THE BEST CONNECTIONS AND HEIGHTS MUST BE DETERMINED BY THE SITE CONTRACTOR.
 - REVIEW ALL ROOMS WITH THE CONSULTANT.
 - FLOOR FINISH SHALL BE 1/2" CONCRETE WITH FINISHES. INFORMATION SHOWN ON FLOOR PLANS SHALL BE APPLIED TO BE APPLICABLE TO THE RELATED SYSTEM SCHEMATIC AND VSD-VISUAL TO PROVIDE A COMPLETE AND OPERATIONAL SYSTEM.
 - VERIFY STRUCTURAL INTEGRITY OF ALL TEMPORARY AND PERMANENT OPENINGS. ADDITIONAL FINISHES TO MAINTAIN STRUCTURAL INTEGRITY SHALL BE INCLUDED UNDER THE CONTRACT.
- PLUMBING AND DRAINAGE NOTES**
- ALL SANITARY DRAINAGE BELOW GRADE SHALL BE MINIMUM 1 1/2" UNLESS INDICATED OTHERWISE.
 - ALL FLOOR DRAINAGE SHALL BE COMPLETE WITH TRAPS AND TRAP PRIMERS.
 - ALL STORM DRAINAGE BELOW GRADE SHALL BE MINIMUM 1 1/2" UNLESS INDICATED OTHERWISE.
 - ALL DOMESTIC COLD WATER AND CONDENSATE HOT WATER PIPES SHALL BE MINIMUM 1/2" UNLESS INDICATED OTHERWISE.
 - ALL PIPING SHALL BE CORROSION RESISTANT TO ADEQUATE OF THE STRUCTURE WITH SUFFICIENT ROOM FOR INSULATION UNLESS INDICATED OTHERWISE. RISE PIPING WITHIN STRUCTURAL STEEL STRAIN WADE FRUNCTION AND BE CROSSED OFFICE AREA.
 - ALL POOL DECK DRAINING TO BE GRADELESS. PROVIDE THE BEST FINISH TO COVER THE QUANTITY OF PIPE INDICATED ON THE DRAWINGS. ANY PIPING ALTERATIONS DUE TO INTERFERENCE OF INSTALLATION SHALL BE ACCOMMODATED BY THE MECHANICAL CONTRACTOR. CONTACT TRADING GROUP TO ELECTRICAL POWER LOCATIONS INDICATED ON THE DRAWINGS OF THE NEAREST GROUP AVAILABLE BY ELECTRICAL.
- POOL NOTES**
- ALL POOL DECK DRAINING SHALL BE PROVIDED.
 - ALL EMERGENCY SHUTOFF SYSTEMS SHALL TURN OFF ALL REGULATION PUMPS INCLUDING FEATURE PUMPS.

